SPECIFICATIONS

T: +44 (0)1933 353 672

sales@sterlingsafetywear.co.uk

W: www.sterlingsafetywear.co.uk







Millington



200 JOULE TOECAP



ANTISTATIC



PENETRATION RESISTANT MIDSOLE



DOUBLE DENSITY SHOCK ABSORPTION



WATER RESISTANT

Non-Metallic, lightweight, waterproof Rigger Boot

item Beseription	
	Brown Nubuck leather upper. Padded collar for added comfort. Composite toe cap and composite midsole protection. 100% non-metallic. Waterproof and breathable inner lining to eliminate water ingress. Dual density PU/Rubber outsole giving heat resistance to 300 degrees centigrade. Anti-Scuff toe guard. PU comfort insole. A lightweight, waterproof, non-metallic rigger boot from DeWalt.
Safety Rating	S3 WR HRO
Slip Rating	SRC
Size Range	5 - 13
Image Name	Millington
Test Standard	CE EN ISO 20345-2011
Brand	DEWALT
Product Range	DEWALT Footwear

SAFETY ICONS EXPLAINED

Item Description



PETROL/CHEMICAL RESISTANT



OIL RESISTANT

ANTISTATIC



HEAT RESISTANT





DOUBLE DENSITY SHOCK ABSORPTION



